

# FIND YOUR OPENER

ALL ASSEMBLIES INCLUDE THE TIP



Granular



Granular + Phos



Liquid



Liquid + Phos

<b>C-SHANK</b>	610-ASY-2711G	610-ASY-2711GP	610-ASY-2711L	610-ASY-2711LP
	610-ASY-2712G	610-ASY-2712GP	610-ASY-2712L	610-ASY-2712LP
<b>EDGE ON BOURGAULT PHD** MORRIS MAXIM</b>	680-ASY-2711G	680-ASY-2711GP	680-ASY-2711L	680-ASY-2711LP
	680-ASY-2712G	680-ASY-2712GP	680-ASY-2712L	680-ASY-2712LP
<b>CASE IH ATX 700 NH P2060 FLEXI-COIL 5500 CONCORD</b>	694-ASY-2711G	694-ASY-2711GP	694-ASY-2711L	694-ASY-2711LP
	694-ASY-2712G	694-ASY-2712GP	694-ASY-2712L	694-ASY-2712LP
<b>CASE IH 800 NH P2070 FLEXI-COIL PD5700</b>	684-ASY-2711G	684-ASY-2711GP	684-ASY-2711L	684-ASY-2711LP
	684-ASY-2712G	684-ASY-2712GP	684-ASY-2712L	684-ASY-2712LP
<b>MORRIS CONTOUR I</b>	683-ASY-2711G	683-ASY-2711GP	683-ASY-2711L	683-ASY-2711LP
	683-ASY2712G	683-ASY2712GP	683-ASY2712L	683-ASY2712LP
<b>MORRIS CONTOUR II</b>	693-ASY-2711G	693-ASY-2711GP	693-ASY-2711L	693-ASY-2711LP
	693-ASY-2712G	693-ASY-2712GP	693-ASY-2712L	693-ASY-2712LP



610-ASY-2712G




680-ASY-2712L



684-ASY-2712G

Fig. 1



Standard Liquid Phosphorus pipe will be 3/16" O.D., for 1/4" O.D. delivery hose will require a 3/16" O.D. compression and 1/4" barb fitting **880-HCL-0001**.

\*\* When installing on a Bourgault PHD use bolt holes pictured in Fig. 1.

## Opener Features:

- Long-wearing carbide-enforced chrome tip is reinforced where you need it – on the nose and wing.
- Hard facing is placed on critical wear points to ensure a long-lasting holder, proper seed placement and virtually no plugging.
- The streamlined holder design combined with the front delivery concept reduces plugging and encourages trash clearance.

**ALL WINGS ON SIDE BAND OPENERS MUST BE POINTING INWARD TO THE CENTER OF THE SEEDING UNIT TO PREVENT PLUGGING WHEN TURNING.**

For a more detailed view of these openers see page 102-103.