



200-GFO-0308

47° SHANK

This "Goosefoot" tillage tool is 5/16" (8 mm) thick and 2-1/2" (63 mm) wide. It is designed specifically for vibrating S-tine cultivators.



**200-SPK-0200
200-SPK-0200ML**

47° SHANK

This quick change spike is 5/8" (15 mm) thick, 2-1/4" (57 mm) wide and 6" (150 mm) long. It has a hardened wear pad (52-56 HRC) for extra life. This tool is ideal for primary tillage or banding fertilizer.

Also available with **MAX LIFE™ Carbide Edge**
200-SPK-0200ML see page 77 for more details.



200-SPK-0215

50° SHANK

This quick change spike is 5/8" (15 mm) thick, 2-1/4" (57 mm) wide and 6" (150 mm) long. It has a hardened wear pad (52-56 HRC) that extends to the top of the stem to prevent wear in abrasive soil or when working at greater depths.



200-SPK-0230

50° SHANK

This quick change spike is 5/8" (15 mm) thick, 2" (50 mm) wide and 4" (102 mm) long. It has a hardened wear pad (52-56 HRC) for extra life. This tool is made specifically for slurry injection.



**200-PWV-0405
200-PWV-0405ML**

47° SHANK

This sweep is 1/4" (6 mm) thick and 4" (100 mm) wide. It is designed mainly for fall tillage or deep working. It has a 3/8" hardened wear pad (52-56 HRC) which increases the life expectancy. The nose on this sweep runs 1/2" (12 mm) lower than the other 200 Series sweeps. This increased pitch improves penetration in hard or compacted ground.

Also available with **MAX LIFE™ Carbide Edge**
200-PWV-0405ML
See page 77 for details.



200-PWV-0428

47° SHANK

This sweep is 5/16" (8 mm) thick and 4" (100 mm) wide. It is designed mainly for fall tillage or deep working. It has a 3/8" x 2" hardened wear pad (52-56 HRC) which increases its life expectancy.



200-PWV-0528

50° SHANK

This sweep is 5/16" (8 mm) thick and 5" (127 mm) wide. It is designed mainly for fall tillage or deep working. It has a 3/8" x 2" hardened wear pad (52-56 HRC) which increases its life expectancy.



200-PWV-0738

50° SHANK

This sweep is 5/16" (8 mm) thick and 4" (100 mm) wide with a 4" wide extended wear pad.



200-PWV-0928

50° SHANK

This sweep is 5/16" (8 mm) thick and 9" (230 mm) wide. It has a 3/8" x 2" hardened wear pad (52-56 HRC) that extends up the entire stem which increases its life expectancy.