

## REVERSIBLE CHISEL

- 5/16" (8 mm) thick and 4" (100 mm) wide.
- 1-3/4" (45 mm) bolt hole spacing to fit light- and medium-duty field cultivators.
- Use mostly for primary tillage in the fall or early spring.



070-RCH-0451

## REVERSIBLE CHISEL

- 5/16" (8 mm) thick and 4" (100 mm) wide.
- 2-1/4" to 2-1/2" (57 to 63 mm) bolt hole spacing.
- Use mostly for primary tillage in the fall or early spring.



070-RCH-0452

## REVERSIBLE SPIKE

- 2" (50 mm) wide, 5/8" (16 mm) thick and 14" (355 mm) long.
- 1-3/4" to 2" (45 to 57 mm) bolt hole spacing.
- Shorter than our other two reversible spikes, it is designed for light- to medium-duty field cultivators or for chisel plows where ground clearance in transport is a concern.



070-RSP-0200A

## REVERSIBLE SPIKE

- 2" (50 mm) wide, 5/8" (16 mm) thick and 17" (431 mm) long.
- 2-1/4" (57 mm) bolt hole spacing.
- Flat through the bolt hole section, it is designed specifically to fit the Bourgault chisel plow as well as the Morris LH 755 shank.



070-RSP-0210A

## REVERSIBLE SPIKE

- 2" (50 mm) wide, 5/8" (16 mm) thick and 16-1/2" (419 mm) long.
- 2-1/4" to 2-1/2" (57 to 63 mm) bolt hole spacing.
- Curved at the bolt hole section, it can be used on any chisel plow shank except the Bourgault and Morris LH 755 shank.



070-RSP-0220A